

Schouwburg Amstelveen tech rider “Kleine Zaal” (Small room)

Dd may 2024

Venue Specs

Curtain	no curtain available
Standard blacks	10x legs 625x200 cm (dark blue velvet) Side blacks (Dark blue velvet) on rails under the side bridge
Full Stage black	1550x600 cm (dark blue velvet) Fixed on rails under the back bridge at 900 cm depth from downstage centre
Cyclorama/ horizon	1400 x 580 cm under the baakbridge 950 cm depth from downstage centre while using the horizon the back passage is closed off.
Stagel	Flat floor Slope 0% Floating keroeing wooden floor Black ballet floor
Scenery	Width From wall to wall 1760cm From side bridge to side bridge 1546cm From legs to legs 1170cm Depth (from downstage centre) Backwall 996cm Front of back bridge 906cm Fixed 'portaaltrek' 0cm Front row seats (incl. legroom) -60cm Front of stands -145cm Hight Ceiling 840cm Bottom of flybars 690cm Bottom of bridges 607cm Bottom of side bridges 497cm
Bridges	<u>zaal</u> , side and back bridges
Load-in/out area	2 indoorplatforms 2 hydraulic <u>tailgates</u> Roller shutters 2.95x2.35cm In The small room we have a loading door at street level: 258x287 cm Trucks can stay parked after consultation

Communication	we use a Clearcom FreeSpeak II system with fixed and wireless belt packs	
Network	In the "kleine zaal" we have comprehensive ethernet connections	
Power	1x 125 A CEE-form Stage right back 1x 125 A CEE-form stage left back 1x 32 A CEE-form stage right back 1x 32 A CEE-form stage left back	
Video	there is a closed video system present in the building, With possibility of monitoring in both rooms	
Front of House	FOH is mid room. Halfway up the stands width 215 cm	
Standard working hours	morning start	10:00 AM
	lunch	12:30 till 01:15 PM
	end of afternoon shift	5.00 PM
	start evening shift	7:00 PM
	Venue opens	8.15 PM
	showtime	8:30 PM
	Showtime matinee	variable
	activity by guest company between 5 and 7 pm after consultation. Green room has bar personnel from from 5PM until end of show interval	

Flybar system

General	since the summer of 2019 we have a semiautomatic/manual flybar system from Unican with 8 flybars, maximum height 6,9 meter Fixed speed is 0,2 m/s	
Kenmerken	lifting load	300 kg
	pointload under steel cables	100 kg
	point load between steel cables	80 kg
	bar length	14.50 meter
	bar section	48 mm
	control panel	remote control stage right
Flybar distances (from downstage centre)	bar 1	roughly 125 cm
	bar 2	roughly 245 cm
	bar 3	roughly 345 cm
	bar 4	roughly 445 cm
	bar 5	roughly 545 cm
	bar 6	roughly 645 cm
	bar 7	roughly 745 cm
	bar 8	roughly 845 cm

Light

Permanent

Dimmers & controls

104 x 2500 Watt Compulite dimmers
DMX-and ethernet patch points on both sides of the floor back and from
and in all bridges (approx 10 patchpoints)

Fixtures

zaalbrug:

15x ETC Lustr x8
4x Ayrton Diablo TC

zijbruggen:

5x ETC Colorsourc Spot V per kant

in Fixed 'portaaltek':

6x ETC Colorsourc Spot V
2x Ayrton Diablo TC

Controlled true network Patch van ELC

Optional

**attention! Described optional materials are used by all venues. Please
contact the stagemanager for more information about availability**

Dimmers & control

1x Roadhog 4 lighting console
1x Hedgehog 4 lighting console
1x ETC Ion xe20

Additional fixtures

10x Desisti 1 kW Fresnell
10x Desisti 2 kW Fresnell
10x Altmann 1 kW zoomprofiel
10x Robert Juliat 1 kW PC
6x 4-bar Thomas 1 kW PAR64
4x 6-bar DTS 1 kW PAR64
16x Thomas 1 kW PAR64

Color gels

standaard Lee colorgamma

moving/Led light

6 x Robe Spider
4 x Robe DL 4
12 x Robe Parfect
8 x AX5 ledspots
8 x Astera AX5 Ledspot
6x Ayrton Diablo TC
8x Ayrton Zonda 3fx

Projection

16 by 9 projection screen 4,88 mtr bij 2,74 mtr
16 by 9 projection screen 7,32 mtr bij 4,11 mtr

Panasonic beamer PT-D 6000 EK 6000 ANSI

Panasonic beamer PT-DZ 870 EK 8000 ANSI
Panasonic beamer PT-RCQ10 10.000 ANSI

Videomixer Blackmagic
Div. video distribution hardware

Audio

Permanent

Amplification

1x d&b R90 interface
1x DAD Penta 721 processor
3x d&b 40D amps

Loudspeakers

(All d&b, All Fixed)

2x 24S / 2x 24S-D - L/R
2x 21S - Sub
1x 24S-D - Center
3x 44S Center – Delay

Inputs

(L/R/C/S)

Analog
AES/EBU
DANTE
Madi

Optional

attention! Described optional materials are used by all venues. Please contact the stagemanager for more information about availability

Grand pianos

Steinway C -227, stemming 440 Herz
Steinway D -274, 'Ludwig', stemming 442 Herz

Mixing consoles

2x Yamaha QL1 + RIO stageracks
Allen & Heath ZED 12FX

Additional amp

1x d&b D20 amp for 4 monitor groups

Monitor speakers

6x d&b M6 Wedge
2x d&b E6 Sidefill/Infill
6x Clair Brothers 12AM
4x Mackie SRM 450
2x Wedge Acoustic line

Outboard gear, Mics and stands

A wide array of outboard gear, mics and stands are available, for more information please contact the stage manager

For more questions please contact our stagemanager: **Youri Bruitzman.**

Available on TEL: 020-5475161 or via email: youri@schouwburgamstelveen.nl